



INTRODUCTION

SiSiB® LR8170 is high strength & transparency type two-component liquid silicone rubber for injection molding process . High performance elastomeric parts could be got through Mixing A: B=1: 1.

KEY FEATURES

Highly transparency

Excellent process ability

High strength

20,30, 40, 50, 60, 70 durometer grades available

ROHS and FDA test passed

TYPICAL PHYSICAL PROPERTIES

| | |
|------------------------|---------------------|
| Product | SiSiB® LR8170 HCE |
| Appearance | Transparent |
| Curing Condition | 130°C×5min, A:B=1:1 |
| Hardness (Shore A) | 66+/-2 |
| Tensile Strength (MPa) | Min. 7.0 |
| Elongation (%) | Min. 300 |
| Tear Strength (KN/m) | Min. 30.0 |

APPLICATIONS

Baby nipples

Swimming goggles

Keypads

Kitchenwares

Power Chemical
ISO9001 ISO14001 certificated

Copyright© 2008 Power Chemical Corporation Ltd.
SiSiB® is a registered trademark of PCC. For more knowledge regarding organosilanes, you may visit www.SiSiB.com or www.PCC.asia



SiSiB® LR8170 LSR

- 2 -

Parts

PACKING AND STORAGE

SiSiB® LR8170 is supplied in 20Kg can or 200Kg drum.

Store in a cool and dry place out of direct sunlight.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: support@SiSiB.com.

Power Chemical
ISO9001 ISO14001 certified

Copyright© 2008 Power Chemical Corporation Ltd.
SiSiB® is a registered trademark of PCC. For more knowledge regarding organosilanes, you may visit www.SiSiB.com or www.PCC.asia